

SSV Metering Devices with Piston Detector for Electronic Monitoring

Product survey



Technical data - SSV metering devices with piston detector (N)

		Unit
Outlets	Qty	6 - 22
Pressure		
Max. operating pressure	[bar]	350
Max. differential pressure	[bar]	100
Output		
per outlet and stroke	[cm ³]	0,2
Outlet thread		M 10 x 1
Material		
Steel		Surface, black chromate-treated
Stainless steel		1.4305
Stainless steel		1.4571, for SSV6-12
Temperature		
Operating temperature	[°C]	-25 to +75

Dimensions

Outlets	Width	Width	Depth
6	60	60	30
8	75	60	30
10	90	60	30
12	105	60	30
14	120	60	30
16	135	60	30
18	150	60	30
20	165	60	30
22	180	60	30

All lengths dimensions in mm

SSV metering devices with piston detector for electronic monitoring

Outlets	Inlet thread 1/8" female		Inlet thread 1/8" NPT female
	Material	Material	Material
	Steel	Stainless steel 1.4305	Steel
6	619-28257-1	619-29003-1	619-28653-1
8	619-28258-1		619-28654-1
10	619-28259-1	619-28529-1	
12	619-28260-1	619-29004-1	
14	619-28890-1	619-77088-1	
16	619-28907-1	619-77617-1	
18	619-28957-1		
20	619-28935-1		619-28937-1
22	619-29015-1		